









# Rückenleisten | Backplates (RLC)



Rückenleisten für Concorde (RLC) (gewölbt)	Backplates for Concorde (RLC) (curved)	Contre-plaques pour Concorde (RLC) (arrondies)	Contra-placas para Concorde (RLC) (redondas)								
A Breite B Länge C Höhe der Niete	A Width B Length C Height of rivet	A Largeur B Longueur C Hauteur des rivets	A Ancho B Longitud C Altura del remache								
A / B / C									kg /1000	m³ /Karton	TM
RLC 25/181/10 **	COR	20, 25	171,0	25,0	181,0	107,9	400	32.400	16,9	0,0176	
RLC 28/181/10 **	COR	25	171,0	28,0	181,0	107,9	400	32.400	19,5	0,0176	
RLC 37/181/10 **	COR	30	171,0	37,0	181,0	107,9	250	20.250	30,0	0,0176	
RLC 16/226/08 *	COR	13, 16	216,0	16,0	226,0	207,0	600	48.600	13,6	0,0176	
RLC 25/226/10 **	COR	20, 25	216,0	25,0	226,0	172,0	300	24.300	21,3	0,0176	
RLC 28/226/10 **	COR	25	216,0	28,0	226,0	172,0	300	24.300	23,8	0,0176	

\* für Folienstärke bis 0,8 mm

\* for boardthickness up to 0,8 mm

\* pour une épaisseur de couverture jusqu'à 0,8 mm

\* para espesor de tapa 0,8 mm

\*\* für Folienstärke bis 1,5 mm

\*\* for boardthickness up to 1,5 mm

\*\* pour une épaisseur de couverture jusqu'à 1,5 mm

\*\* para espesor de tapa 1,5 mm