



# File (F)



Hebelmechanik - F  
Niederhalter - FCO  
schwarzer Drücker  
Einschubgrundplatte - FPL

Lever Arch Mechanism - F  
Compressor bar - FCO  
black button  
Slide-in-plate - FPL

Mécanisme à levier - F  
Compresseur - FCO  
bouton noir  
Plaque-export - FPL

Mecanismo de palanca - F  
Compresor - FCO  
botón negro  
Placa de exportación - FPL

	ABC							kg /1000	m <sup>3</sup> /Karton	TM
F 50 <sup>1,2,3</sup>	A	80	35	50	4,0	300	7.200	70,0	0,0549	
F 70 <sup>1,2,3</sup>	A	80	56	72	4,0	200	4.800	80,0	0,0514	
F 80 <sup>1,2</sup>	A	80	63	79	4,0	200	4.800	85,0	0,0575	
FCO metal	A					1.000	48.000	8,5	0,0288	
FCO plastic	A					1.000	48.000	11,4	0,0288	
FPL <sup>4</sup>	D					1.000	30.000	17,5	0,0288	

<sup>1</sup> Lochbild  
<sup>1</sup> Hole pattern  
<sup>1</sup> Perforation  
<sup>1</sup> Perforación

	a	b	c	d
G 3,8	83,5	53,0	31,5	3,8
G 4,5	83,5	53,0	31,5	4,5
E 3,8	83,5	54,1	32,0	3,8
E 4,5	83,5	54,1	32,0	4,5

<sup>2</sup> "Premium" Grundplatte mit 0,8 mm Dicke möglich ("Standard" 0,6 mm) / „premium“ base plate with thickness 0,8 mm possible („standard“ 0,6 mm)

<sup>3</sup> mit kurzem Hebel möglich / possible with short lever

<sup>4</sup> auf Anfrage / on request

